

Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: WACKER CATALYST PASTE T 40

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Intermediate chemical

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor:

Street/POB-No.:

State/postal code/city:

Telephone:

Telefax:

DRAWIN Vertriebs-GmbH
Rudolf-Diesel-Straße 15
D 85521 Riemerling
+49 89 60869-0
+49 89 60869-250

Information about the Safety Data Sheet: Telephone +49 8677 83-4888
Telefax +49 8677 886-9722

eMail WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information: +44 1273 289451

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Hazard class	Hazard category	Route of exposure	H-Code
Specific target organ toxicity - repeated exposure	Category 2		H373
Specific target organ toxicity - single exposure	Category 3		H335
Flammable liquids	Category 3		H226
Serious eye damage/eye irritation	Category 2		H319

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008:

Pictogram(s):







Signal Word: Warning

H-Code	Hazard Statements
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Page: 1/11



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

P-Code	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection.
P243	Take action to prevent static discharges.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
P338	do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to waste disposal.

Hazard ingredients (labelling):	
Tetraethyl silicate	
Bis(neodecanoyloxy)dioctylstannane	

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 16,92 %.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Organotin compound + Silicic acid ester + auxiliary

3.2.2 Hazardous ingredients

Type	CAS No.	EC-No. REACH no.	Substance	Content %	Classification according to Regulation (EC) No. 1272/2008*	Comment
INHA	78-10-4	201-083-8 01-2119496195-28	Tetraethyl silicate	<40	Flam. Liq. 3; H226 Acute Tox. 4 by inhalation; H332 Eye Irrit. 2; H319 STOT SE 3; H335	[1], [2]
INHA	68299-15-0	269-595-4	Bis(neodecanoyloxy)dioctylstan nane	<20	Aquatic Chronic 4; H413 STOT RE 2; H373	[1]

Type: INHA: ingredient, VERU: impurity

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance

*Classification codes are explained in section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

SECTION 4: First aid measures



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

4.1 Description of first aid measures

General information:

Take persons to a safe place. Observe self-protection for first aid. Seek medical advice in the event of contact with this substance.

After contact with the eyes:

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice and clearly identify substance.

After contact with the skin:

Wipe off excess material with cloth or paper. Remove contaminated or soaked clothing. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice and clearly identify substance.

After inhalation:

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. Seek medical advice and clearly identify substance.

After swallowing:

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice and clearly identify substance.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

alcohol-resistant foam, carbon dioxide, water mist, sprinkler system, sand, extinguishing powder.

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes .

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Page: 3/11



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Spilled substance increases risk of slipping. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Observe information in section 8. Keep away from incompatible substances in accordance with section 10.

Precautions against fire and explosion:

Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

CAS No.	Substance	Type	mg/m³	ppm	Dust fract.	Fibre/m ³
78-10-4	Tetraethyl silicate	TLV_GB	87,0	10,0		
78-10-4	Tetraethyl silicate	EU	44,0	5,0		
64-17-5	Ethanol	TLV_GB	1920,0	1000,0		

Derived No-Effect Level (DNEL):

Tetraethyl silicate

rotractify chicate	
Area of use:	Value:
Worker; dermal; systemic (acute)	12,1 mg/kg/day
Worker; dermal; systemic (long term)	12,1 mg/kg/day
Worker; by inhalation; systemic (acute)	85 mg/m³
Worker; by inhalation; local (acute)	85 mg/m³
Worker; by inhalation; systemic (long term)	85 mg/m³

Page: 4/11



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

Worker; by inhalation; local (long term)	85 mg/m³
Consumer; dermal; systemic (acute)	8,4 mg/kg/day
Consumer; dermal; systemic (long term)	8,4 mg/kg/day
Consumer; by inhalation; systemic (acute)	25 mg/m³
Consumer; by inhalation; local (acute)	25 mg/m³
Consumer; by inhalation; systemic (long term)	25 mg/m³
Consumer; by inhalation; local (long term)	25 mg/m ³

Predicted No Effect Concentration (PNEC):

Tetraethyl silicate

Area of use:	Value:
reshwater	0,192 mg/l
	The value has been derived for the following hydrolysis product:
	ethanol
marine water	0,0192 mg/l
	The value has been derived for the following hydrolysis product:
	ethanol
Sediment (freshwater)	0,18 mg/kg wet weight
	The value has been derived for the following hydrolysis product:
	ethanol
Sediment (marine water)	0,018 mg/kg wet weight
	The value has been derived for the following hydrolysis product:
	ethanol
Soil	0,05 mg/kg wet weight
	The value has been derived for the following hydrolysis product:
	ethanol
sewage treatment plant	4000 mg/l
	The value has been derived for the following hydrolysis product:
	ethanol
ntermittent release	10 mg/l
	The value has been derived for the following hydrolysis product:
	ethanol

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not inhale gases/vapours/aerosols. Use with adequate ventilation. Avoid contact with eyes and skin. Preventive skin protection recommended. Remove contaminated, soaked clothing immediately. Clean work areas regularly. Provide emergency shower and eye-bath. Do not eat, drink or smoke when handling. Keep away from foodstuff, drink and feedingstuff.

Personal protection equipment:

Respiratory protection

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

For long or intense exposure, use respiratory protective equipment. Suitable respiratory equipment: Positive pressure self contained breathing apparatus, according to acknowledged standards such as EN 137.

Observe the equipment manufacturer's information and wear time limits for respirators.



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

Eye protection

tight fitting protective goggles.

Hand protection

Protective gloves are required at all times when handling the material, according to recognized standards such as EN374.

Recommended glove types: Protective gloves made of butyl rubber

thickness of the material: > 0,3 mm Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Skin protection

Vapour density

9.1

If handled uncovered: Chemical protective clothing, full-body liquid-tight protection if necessary. Please observe the instructions regarding permeability time which are provided by the supplier.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil. Observe local waste water bye-laws for organo tin and tin compounds. Do not introduce large amounts into purification plants.

8.3 Further information for system design and engineering measures

Information on basic physical and chemical properties

Observe information in section 7. Observe national regulatory requirements.

Water solubility / miscibility virtually insoluble

Relative gas/vapour density No data known.

SECTION 9: Physical and chemical properties

Property:	Value:	Method:
Appearance		
Physical state:	liquid	
Form		
Colour:	red	
Odour		
Odour:	faint	
Odour limit		
Odour limit	no data available	
pH-Value		
pH-Value	not applicable	
Melting point/freezing point		
Melting point / melting range	not determined	
Initial boiling point and boiling range		
Boiling point / boiling range	not applicable	
Flash point		
Flash point:	55 °C	(ISO 2719)
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Vapour pressure		
Vapour pressure	not determined	
Solubility(ies)		



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

Relative Density

(DIN 51757)

Partition coefficient: n-octanol/water

Partition coefficient: n-octanol/water..... No data known.

Auto-ignition temperature

Decomposition temperature

Thermal decomposition not applicable

Viscosity

Viscosity (dynamic) not applicable

Molecular mass

Molecular mass not applicable

9.2 Other information

Solubility in water: Hydrolytic decomposition occurs. Hydrolysis products reduce the flash point.

SECTION 10: Stability and reactivity

10.1 - 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

Moisture, heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts with water, basic substances and acids. The reaction takes place with the formation of alcohols.

10.6 Hazardous decomposition products

If stored and handled properly: none known. Alcohols under the effect of humidity, water and protic agents.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Acute toxicity estimate (ATE):

ATE_{mix} (Oral): > 2000 mg/kg

11.1.2 Skin corrosion/irritation

Assessment:

Based on the available data a clinically relevant skin irritation hazard is not expected.

Product details:

Result/Effect	Species/Test system	Source
No skin irritation	Rabbit	test report

11.1.3 Serious eye damage / eye irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

11.1.4 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Further toxicological information

Ethanol (64-17-5) is readily absorbed at all exposure routes. Ethanol may cause irritation of eyes and mucosa, trigger dysfunction of the central nervous system and cause nausea as well as dizziness. Chronic exposure to high amounts of ethanol may cause damage to liver and central nervous system.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

For the product as a whole, no test data is available.

12.2 Persistence and degradability

Assessment:

The hydrolysis product (Ethanol) is readily biologically degradable. Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

No data known.

12.4 Mobility in soil

Assessment:

For the product as a whole, no test data is available.



Material: 60081733 **WACKER CATALYST PASTE T 40**

Date of print: 07.10.2021 Version: 3.5 (GB) Date of last alteration: 24.08.2020

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

SECTION 13: Disposal considerations

Waste treatment methods

13.1.1 Material

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

SECTION 14: Transport information

14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation:	Dangerous Goods
14.1 UN no:	1993
14.2 Proper Shipping Name	Entzündbarer flüssiger Stoff, n.a.g. (Enthält Tetraethylsilicat)
14.2 Proper Shipping Name (national):	Flammable liquid, n.o.s (Contains Tetraethyl silicate)
14.3 Class	3
14.4 Packaging Group	III

· · · · · · · · · · · · · · · · · · ·	•••
Railway RID:	
Valuation:	Dangerous Goods
14.1 UN no	1993
14.2 Proper Shipping Name	Entzündbarer flüssiger Stoff, n.a.g. (Enthält Tetraethylsilicat)
14.2 Proper Shipping Name (national):	Flammable liquid, n.o.s (Contains Tetraethyl silicate)
14.3 Class	3
14.4 Packaging Group:	III

Transport by sea IMDG-Code:

Valuation:	Dangerous Goods
14.1 UN no:	1993
14.2 Proper Shipping Name	Flammable liquid, n.o.s. (Contains Tetraethyl silicate)
14.3 Class	3
14.4 Packaging Group	III

Air transport ICAO-TI/IATA-DGR:

Valuation:	Dangerous Goods
14.1 UN no	1993
14.2 Proper Shipping Name	Flammable liquid, n.o.s. (Contains Tetraethyl silicate)
14.3 Class	3
14.4 Packaging Group	III



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

14.5 Environmental hazards

Hazardous to the environment: no Marine Pollutant (IMDG): no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances (Seveso III):

Listed in Directive	Ser. number in list	Qualifying Quantity 1	Qualifying Quantity 2
FLAMMABLE LIQUIDS	P5c	5.000 t	50.000 t

Relevant regulations:

SI 2002/1689: CHIP Regulations 2002 SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

Other specifications, restrictions and prohibitions:

REACh Annex XVII: This product contains dioctyltin compounds in an amount of over 0.1 wt.%. Annex XVII, entry 20, of regulation 1907/2006, in its current version, must be taken into account.

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Banned and/or restricted

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan : ENCS (Handbook of Existing and New Chemical Substances):

This product is listed in, or complies with, the substance inventory.

Australia : AICS (Australian Inventory of Chemical Substances):

This product is listed in, or complies with, the substance inventory.

China : IECSC (Inventory of Existing Chemical Substances in China):

This product is listed in, or complies with, the substance inventory.

Canada :: DSL (Domestic Substance List):

United States of America (USA) TSCA (Toxic Substance Control Act Chemical Substance Inventory):

All components of this product are listed as active or are in compliance with the

substance inventory.



Material: 60081733 WACKER CATALYST PASTE T 40

Version: 3.5 (GB) Date of print: 07.10.2021 Date of last alteration: 24.08.2020

Taiwan: TCSI (Taiwan Chemical Substance Inventory):

This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of

this obligation.

European Economic Area (EEA) REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

South Korea (Republic of Korea)...... AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"):

Please approach your regular WACKER contact for more detailed information.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Explanation of the GHS classification code:

Flam. Liq. 3; H226.....: Flammable liquids Category 3; Flammable liquid and vapour.

Acute Tox. 4; H332: Acute toxicity Category 4; Harmful if inhaled.

Eye Irrit. 2; H319 Serious eye damage/eye irritation Category 2; Causes serious eye irritation.

STOT SE 3; H335: Specific target organ toxicity - single exposure Category 3; May cause respiratory irritation.

Aquatic Chronic 4; H413 Long-term (chronic) aquatic hazard Category 4; May cause long lasting harmful effects to aquatic life.

.....:

STOT RE 2; H373: Specific target organ toxicity - repeated exposure Category 2; May cause damage to organs through

prolonged or repeated exposure.

Classification	Rationale:
Specific target organ toxicity - repeated exposure, Category 2	Calculation method
Specific target organ toxicity - single exposure, Category 3	Calculation method
Flammable liquids, Category 3	On basis of test data.
Serious eye damage/eye irritation, Category 2	Calculation method

- End of Safety Data Sheet -