

Product Type and Description: PZ-A 428AR

Precizioned SculptaCast™ PZ-A 428AR is a general grade red sculpture wax ideal for painting and slush casting. Its low viscosity and excellent flow characteristics allow for painting and slushing of fine detail. As well, its moderate set rate provides the capability of being effectively used as a backup wax. SculptaCast™ 428AR offers moderate rigidity and high polishing capability. This product is easily adaptable and readily blends with other sculpture waxes in our product line to obtain specific desired properties or creating your own custom blend. The product is based from high quality petroleum raw materials providing consistent results and is naturally clean burning with very low ash residue.

Key benefits

- General Purpose for creating simple or detailed wax patterns
- Firm and rigid buildup with slight ductility.
- Hard and dry aspect allows for superior polishing.



Physical Properties

Testing Procedure/Method

Softening Point, Ring and Ball @4°F/min (IPCS 004)

Drop Melt Point @4°F/min (IPCS 005)

Flow Test >50% (IPCS 007)

Needle Penetration 100 g @77°F (IPCS 006)

Apparent Viscosity, Brookfield Thermosel @200°F (IPCS 009)

Ash Content (IPCS 002)

Color (IPCS 020)

Typical Properties
144°F
154°F
38°C
10.0 dmm
14.5 cps
0.005%
Red

Precizioned Ltd has determined test method and provided analysis as noted herein. The levels referenced herein are only for general guidance and do not constitute a firm specification. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user. All potential liability related to the sale and use of this product is limited to the cost of the particular goods sold in their respective transactions.



1570 Terex Road Hudson Ohio 44236 USA Tel: +1 330 342 0407 Tel: +44 (0)207 831 3111 Email: cjoseph@ipcs-uk.com

www.Precizioned.com

Product Data Sheet

Document Revision: 1